



- 600-2000 Tenants
- 2500-3500 cards and access codes
- Programming:
 - Local via Keypad or RS232
 - Remote via dial-up modem
- Programming and Data Management with AeGIS Management Software
- Event recording with 1200 events buffer.
- 2 x 16 Electronic Liquid Crystal Display (LCD)
- Two relays
- Non-Volatile Memory
- Auto Unlock Timer, Time Zones, and Holiday Time Zones
- Optional 26-Bit Wiegand Reader
- Indoor or outdoor, surface and full-flush mount
- Brushed Stainless Steel Face

Warranty: 24 months

SPECIFICATIONS

POWER INPUT: 12VAC/40VA (supplied) or 12-VDC/40VA with battery backup charging circuit.

CURRENT CONSUMPTION: 700mA idle, 900mA operating.

OPERATING ENVIRONMENT: 32°F to 140°F. *Heater is required if the temperature is below 32°F.*

NIGHT LIGHT: Super Bright Light Emitting Diode (LED).

COMMUNICATION: 1200 Baud Modem, RS-485 and RS-232.

CONSTRUCTION: 16 Gauge Cold Rolled Steel back box with enamel finished and Brushed Stainless Steel Faceplate

MOUNTING: Surface and full-flush.

DIMENSIONS:

Surface 13-9/16"(H) x 11-1/4"(W) x 3-3/4"(D)

Full-flush 13-7/8" (H) x 11-9/16"(W) x 3-3/4" (D)

MOUNTING RING FULL-FLUSH (FFM9 is included):

Inside 13-3/4" (H) x 12" (W) x 3-11/16" (D)

Outside 18" (H) x 15-5/8" (W)

SHIPPING WEIGHT: 16 lb - 21 lb

See quick guide or manual for further specifications

ORDERING PART

Surface Mount

9600CR25P

600 tenants 25000 cards/codes

92KCR35P

2000 tenants 3500 cards/codes

Full-flush Mount

9600CR25FFP

600 tenants 2500 cards and/or codes

92KCR35FFP

2000 tenants 3500 cards and/or codes

ACCESSORIES

26-Bit Wiegand Proximity Readers and cards

UWCR Wiegand Proximity Reader.

UIISO credit card size (passive card)

UCLAM Clam Shell (passive card)

UFOB Key Fob (passive fob)

Satellite Systems

USCR RS-485 Satellite Card Reader

USKP RS-485 Satellite Keypad

UCRM 26 Bit Wiegand RS-485 Controller Module

Video Package

UVPC Color Camera Package.

UVPB Balun for twisted pair video transmission

Pedestal Mounting Post, Adapter Plate and Mounting Ring

UPM1S Standard Single Arm (42"H, 5"x5" base)

UPM4S Standard Single Arm (47"H, 5"x5" base)

UPM1L Large Single Arm (47"H, 8"x8" base)

UPM6L Large Single Arm (64"H, 8"x8" base)

UPM2 Double Vertical Arm (44"/84"H, 8"x8" base)

UPM5 Double Horizontal Arm (47"H, 8"x8" base)

UPMDB64 Single Arm Direct Buriel (64"H)

UAP09 Adapter Plate AeGIS 9000P Series

UPM12E 12" Expansion Arm use for all UPM

Miscellaneous Accessories

FFM9 Full-flush mounting ring, *included w/ system*

USP1 AC and Telephone Surge Protector.

AHP5 Heater Pad with Thermostat.

UBAT1 12VDC 4.5 Amp Hour backup battery.

UXIT Multipurpose push button switch

AMDM 56K Desktop/Laptop Modem

Specifications subject to change without prior notice