

QUANTUM • QR5IP

IP INTERNET PROGRAMMABLE RESIDENTIAL AND SMALL MULTI TENANT TELEPHONE ENTRY



- Internet IP programmable via any browser on the market including iPad, Smartphone and Tablet
- Single residential or 10 unit multi-tenant application
- Programmable via Local Area Network (LAN), INTERNET or Ethernet Direct Connection via any browser
- **“NO SOFTWARE INSTALLATION”** on a computer is necessary
- Dedicated or existing telephone line
- 100 (4-8 digit) code, 100 card and 100 transmitter
- 10 programmable limited use access codes or cards
- 10 programmable open hold codes or cards
- Built-in 26 Bit Wiegand Reader and Radio Receiver
- 10 call forwarding phone numbers
- Automatic call forwarding and call waiting (intercom mode)

- 10 auto unlock timer, 10 time zone and 20 holiday time zone
- Comprehensive Event Reports
- Built-in 26 Bit Wiegand Reader and Radio Receiver
- Up to eight optional satellite reader or keypad with independent access to each satellite

SPECIFICATIONS

POWER INPUT: 12-18VAC/DC 40VA UL Listed Transformer (12VAC Transformer is supplied).

CURRENT CONSUMPTION: 750mA Idle, 1000mA operation.

EMERGENCY BATTERY INPUT: Built-in Charging circuit for 12VDC Battery 4Ahr (battery is not supplied)

OPERATING ENVIRONMENT: 0°F to +140°F. Relative Humidity 0% to 95%.

MOUNTING: Surface, Indoor or outdoor.

RELAY OUTPUT: Two From C Dry Contact 120VAC 10A/ 24VDC 10 A/ 250VAC 7A programmable output duration 01-99 seconds.

TWO AUXILIARY INPUT AND DOOR SENSOR

CONSTRUCTION: 16 Gauge Cold Rolled Steel with Brushed Stainless Steel Faceplate.

DIMENSION: 6-7/16" (H) x 10" (W) x 2-1/16" (D)

WEIGHT: 6 lbs.

WARRANTY: 24 months

ORDER PART NUMBER

QR5IP

ACCESSORIES

[Pedestal Mounting Post, Adapter Plate and Mounting Ring](#)

UPM1S Standard Single Arm (42"H, 5"x5" base)

UPM4S Standard Single Arm (47"H, 5"x5" base)

UPM1L Large Single Arm (47"H, 8"x8" base)

UPM6L Large Single Arm (64"H, 8"x8" base)

UPM8L Large Single Arm (84"H, 8"x8" base)

UPM2 Double Vertical Arm (44"/84"H, 8"x8" base)

UPM5 Double Horizontal Arm (47"H, 8"x8" base)

UPMDB64 Single Arm Direct Buriel (64"H)

UPMDB72 Single Arm Direct Buriel (72"H)

UAP78 Adapter Plate AeGIS 8000P Series

UPM12E 12" Expansion Arm use for all UPM

UVPC Analog color camera

QRT Radio transmitter FOB

UFOB Quantum Keyfob

UCLAM Quantum Clam Shell Card

UIISO Quantum ISO Card

USP1 AC and Telephone Surge Protector

USCR 26-Bit Wiegand Satellite Card Reader

USKP Satellite keypad

UMCK Universal Master Card Reader/Keypad

UCRM 26-Bit Wiegand/RS-485 controller Module

AXIT Push button switch

Specifications and Warranty subject to change without prior notice

PACH AND COMPANY

Home of Telephone Access Control Systems

AEGIS QUANTUM

Phone: 1-888-678-7224

949-498-2951

www.pach-co.com